

PERSONAL PROTECTIVE EQUIPMENT



MAJOR HIGH CUT

Article No.: 73110CV544 Model No.: 8938-4

Cavalier™ Major Safety Boots with Electrical Hazard Protection designed to give the user additional protection while working in places where the chance of exposure to electrical currents is high. The soles provide a safety barrier to protect from open electrical currents up to 20 Kilovolts. Comfortable, lightweight and 100% water resistant.





COMPOSITION:

- Safety Boots S3 made in Genuine Waterproof Leather
- 100% Metal Free.
- Good Design, comfortable, antislip, light & flexible.
- HRO Certification (resistant up to 300°C per contact)

FEATURES:

Upper: Waterproof AIRCELL Leather Lining: Black 3D Mesh Lining (Polyester)

Composite toe cap - 200J Resistant Toe Cap Toecap:

according to EN 12568:2010

Insole: Antistatic + Anti-bacterial foam

EVA + Nylon lining

Midsole: APT (Antiperforation Textile)

Double Density PU/RUBBER (Direct Injection) **Outersole:**

Heel Stiffener: Thermoplastic

EN ISO 20345:2011 CE Standard:

S3 SRC HRO **Category:**

Color: Black

Sizes: 36-48 (Europe)

Also available in **MAJOR LOWCUT** Art. No. 74110CV543 Model No. 8937-4





IMPACT RESISTANT









ANTIPERFORATION



CATEGORY DESCRIPTION

\$3 200 Joule Toecap Protection. Closed seat region (fully enclosed heel). Antistatic properties. Energy absorption of seat region. Water penetration and water absorption resistance. Plus penetration resistance. Cleated outsole.



This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in prohibited without written approval. FT FW 9005-3.2

BORN TOUGH



PERSONAL PROTECTIVE EQUIPMENT





MAJOR HIGH CUT

Article No.: 73110CV544 Model No.: 8938-4

> High Abrasion Resistant, Anti-static & Anti-slip

> > **Double Density PU/RUBBER SRC HRO**

(resist up to 300 °C)

Protect against open electrical current up to 20,000kV

Shock absorber

PU overcap



TECHNICAL SPECIFICATIONS

Plastic shoelace

eyelets

Upper textile

Pull tab

Polyester shoelace with plastic tip aglets

Red contrast

Waterproof Smooth AIRCELL Leather



ANTIPERFORATION



Composite toe cap S3 - Resistant 200J



100% No Metal





37

5



_7	г

SHOE SIZE CHART AS PER EUROPEAN STANDARDS											
7	38	39	40	41	42	43	44	45	46	47	48
	5	6	6.5	7	8	9	10	10.5	11	11	13



CATEGORY DESCRIPTION

\$3 200 Joule Toecap Protection. Closed seat region (fully enclosed heel). Antistatic properties. Energy absorption of seat region. Water penetration and water absorption resistance. Plus penetration resistance. Cleated outsole.

3

EU







Doc. Control:	Rev.:	Date:	
	3.2	April 9, 2016	

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT FW 9005-3.2