



COMMANDER

Article No.: 75110CV229

Model No.: 8619-4

Cavalier™ Commander Rigger Boots offer the maximum protection. Designed with high quality waterproof leather, so feels incredibly comfortable on your foot, ankle and calf. Safety Boots features steel toecap & steel midplate. Antislip, lightweight and 100% water resistant.



COMPOSITION:

- Safety Rigger Boots made of Waterproof Natural Full Grain Leather
- Steel toe-cap and midplate
- Good Design, comfortable, antislip, light.

FEATURES:

- Upper:** Waterproof Natural Full Grain Leather
- Lining:** Breathable lining
- Toecap:** Steel Toe – Resistant 200J
- Midsole:** Steel midplate according to **EN 12568:2010**
- Insole:** Antistatic + Anti-bacterial foam
EVA + Nylon lining
- Sole system:** Double Density PU/TPU direct injection
- Heel striffener:** Thermoplastic
- Norm:** **EN ISO 20345:2011 CE**
- Category:** **S3 SRC**
- Color:** Dark Brown
- Height:** 28 cm (sole to collar)



IMPACT RESISTANT



PENETRATION RESISTANT



SLIP RESISTANT



OIL RESISTANT



ABRASION RESISTANT

Category Description

S3 200 Joule Toecap Protection. Closed seat region (fully enclosed heel). Antistatic properties. Energy absorption of seat region. Water penetration and water absorption resistance. Plus penetration resistance. Cleated outsole.



STEEL TOE CAP



STEEL MID PLATE

SHOE SIZE CHART AS PER EUROPEAN STANDARDS										
EU	39	40	41	42	43	44	45	46	47	48
UK	6	6.5	7	8	9	10	10.5	11	12	13

Doc. Control:	Rev.:	Date:
	3.2	April 9, 2016

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT FW 9012-3.2

BORN TOUGH

A PRODUCT OF





COMMANDER
 Article No.: 75110CV229
 Model No.: 8619-4

COMMANDER

TECHNICAL SPECIFICATIONS



STEEL MID PLATE
 EN 12568:2010



IMPACT RESISTANT



PENETRATION RESISTANT



SLIP RESISTANT



OIL RESISTANT



ABRASION RESISTANT



Anatomic & Antistatic



PU Polyurethane is a synthetic soling material. It is flexible and lightweight. Resistant to 130°C heat, oil, low concentration acids/alkalis and solvents.

S3 200 Joule Toecap Protection. Closed seat region (fully enclosed heel). Antistatic properties. Energy absorption of seat region. Water penetration and water absorption resistance. Plus penetration resistance. Cleated outsole.

SRC Passes SRC slip resistant standards: tested on ceramic tile contamination with a dilute soap solution and smooth steel contamination with glycerol.

Doc. Control:	Rev.:	Date:
	3.2	April 9, 2016

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT FW 9012-3.2

BORN TOUGH

A PRODUCT OF

 PROTECTIVE LINE