



AV-SG25 SAFETY EYEWEARS

Article No.: 602AV116

This safety glass design has long been the best selling commodity style, and it has met with worldwide acceptance.

This model has adjustable temples and universal nose bridge.

Meets ANSI Z97.1 and CE EN-166.



AV-SG25 C



AV-SG25 G



AV-SG25 WS3



AV-SG25 WS5

LENS STYLE

APPLICATION & BENEFIT



Clear - General purpose impact protection for indoor and outdoor use.



Grey - General purpose sun lens that reduces sun glare and intense sunlight for outdoor applications.



Weld Shade 3 - Torch brazing and light gas cutting.



Weld Shade 5 - Torch brazing and light gas welding and cutting.

TECHNICAL SPECIFICATION

| | |
|-----------------------------------|-----------------|
| Lens thickness | : 2.2 mm |
| PD | : 68 mm |
| Lens Base | : 4 curve |
| Weight | : 35 gm |
| Lens size vertical | : 62 mm |
| Lens size diagonal | : 62.67 mm |
| Bridge | : 32.25 mm |
| Temple length (lens-tip) | : 99.6~112.43mm |
| Overall Width (hinge-hinge) | : 138.9 mm |
| Closest point between lens | : N/A, Single |
| Closest point between temple tips | : 114.53 |

STANDARDS



Safety glasses comply with **ANSI Z87.1-2010** and most models meet the requirements of **CE - EN166**. Required test include among others high velocity, high mass impact, lens thickness, lens distortion, and lens light transmission.

| | | |
|---------------|-------|---------------|
| Doc. Control: | Rev.: | Date: |
| | 3.2 | April 5, 2016 |

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT EF 2012-3.2



A PRODUCT OF

