



CORDED EAR PLUGS AV-416

Article No.: 2474AV489

The AVES® AV-416 is a fully metal detectable corded reusable ear plug. Designed to be used over and over again, with maintained comfort and effectiveness.

Has 27NRR/34SNR



27dB NRR, 34 dB SNR, Protection Level: 92 - 108 dB

Shape/Dimensions: Tapered shape, 4 flanges, 30mm long, 14mm at widest point.

Earplug: Injected mix of SEBS (Styrene-Ethylene-Butylene-Styrene) with tiny metal flakes (embedded)

Cord: Injected mix of PVC and tiny metal flakes (embedded)

Non allergenic material. **Standard Colors:** Blue **Weight:** 2.2 g/pair

Packaging: 100 pairs/box, 4 boxes/carton

Best for Food Handling Industries!



FEATURES

- Contoured 4-flange, ultra-soft polymer design puts morematerial in contact with ear canal. Delivers all-day comfort, superior attenuation.
- Built-in, firm handle allows user to direct the angle of insertion, adapting to each ear canal.
- Advanced Non-allergenic polymer material is non-irritating, resistant to ear wax and body oils; outlasts PVC ear plugs.
- Wash and reuse for several weeks without losing its attenuation, comfort and effectiveness.
- Universal size, self-contours to fit virtually any shape of ear canal, accommodates diverse workforce to simplify inventory control.

-1974	9	Frequency, Hz	125	250	500	1000	2000	3150	4000	6000	8000	NRR
3-19	AV-41	Mean Attenuation dB	35.7	33.2	35.7	36.1	37.5	39.9	38.8	41.6	45.5	27
NSI S3		Std. Deviation	4.1	4.6	4.3	4.5	3.5	4.1	4.3	3.3	4.4	
4									_			

_													
CE EN-352-2:2002		Frequency, Hz	125	250	500	1000	2000	4000	8000	Н	М	L	SNR
	AV-416	Mean Attenuation dB	34.0	30.8	35.1	36.9	36.7	36.5	42.5		32	30	34
		Std. Deviation	4.7	3.6	4.6	4.9	4.5	4.1	4.3	33			
		MEAN - SD	29.2	27.3	30.5	32.0	32.3	32.4	38.2	W			

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT EP 3030-3.2