





AV-HB650 EAR MUFFS

Article No.: 2536AV482

High performance ear muff delivers full spectrum attenuation as well as low frequency attenuation from the extra deep ear cups. Offers 29 NRR and 34 SNR! Meets ANSI S3.19-1974 standards.





DESCRIPTION

- 29 dB NRR from certified US laboratory ANSI S3.19-1974
- 34 dB SNR as tested by certified European laboratory to CE EN-352-1
- · Superb full spectrum and low frequency attenuation
- Extra wide ear cushions for highest comfort
- Soft padded headband with low force
- Steel headband tolerates temperature extremes
- Solid construction
- You get the ultimate performance and comfort with this muff

SPECIFICATIONS

Headband

: Stainless Steel

Cushion

: Wide Ear Cushions

Weight

: 10.1 oz./272g

Color

: Black

Noise Reduction Rating

: 29 NRR



AV-SGB30 (Optional) Fits all earmuffs

Mean Attenuation, dB 22.1 27.9 34.9 35.8 37.3 41.4 42.3 41.6 41.2 37 32 27 Std. Deviation 2.9 2.8 3.4 2.0 2.5 2.7 2.8 3.1 3.7	20	Frequency, Hz	125	250	500	1000	2000	3150	4000	6000	8000	Н	М	L	NRR
Std. Deviation 2.9 2.8 3.4 2.0 2.5 2.7 2.8 3.1 3.7	HB6	Mean Attenuation, dB	22.1	27.9	34.9	35.8	37.3	41.4	42.3	41.6	41.2	27	22	27	29
	AV-	Std. Deviation	2.9	2.8	3.4	2.0	2.5	2.7	2.8	3.1	3.7	3/	32	21	29

CE EN-352-1:2002

ANSI S3.19-1974

	Frequency, Hz	63	125	250	500	1000	2000	4000	8000	Н	М	L	SNR
HB650	Mean attenuation, dB	19.3	19.3	26.1	34.0	39.6	35.1	43.5	38.9				
AV-H	Std. Deviation	3.8	2.7	2.8	2.6	3.2	3.0	2.9	5.2	35	32	24	34
∢	Protection	15.5	16.6	23.3	31.4	36.4	32.1	40.6	33.7				

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered Date: under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT EP 3018-3.2 Doc. Control: April 5, 2016