



NES

AV-HB25 EAR MUFF

Article No.: 2536AV60

Most buyers and users of ear muffs are looking for a product that offers great looks, good comfort and attenuation at a reasonable price. The following features needed and wanted by most buyers are offered by AVES® AV-HB25:





Smart foldout storage position

AV-SS25



Normal muff storage position



AV-SGB30 Fits all earmuffs (Optional)

TECHNICAL SPECIFICATIONS

- 25 dB Certified NRR to ANSI S3.19-1974
- 28 dB Certified SNR to CE EN 352-1
- Soft and pliable SuperSeal[™] ear cushions.
- Fully dielectric construction
- Low headband force and light-weight, 6.8 oz.
- SuperSeal™ ear cushions provide outstanding seal & comfort
- · Ease of adjustments with flexible slide clips.
- Dielectric construction
- Color: Blue ear cup other components black
- Weight: 206g (7.3oz)
- Dimension: 195mm(w) x 230mm (h) fully extended

MATERIAL SPECIFICATIONS:

: Dupont Delrin Acetal Headband

125

: ABS Ear cup Volume ring : ABS Slide clip : PUR

Foam Absorber Ear cushion	: Urethane : PVC/Polyeste

Frequency, Hz AV-HM25 Mean Attenuation, dB

AV-SS25 Support Strap (Optional)	Fits all ear	Fits all earm (Optional)							
CONSTRUCTION									
HEAD BAND	FOAM INSERT EAR CUSHION FOAM INSERT VOLUME RING								

ANS		Std. Deviation	2.0	1./	1.8	1.8	2.0	2.2	2.9	4.0	2.1				
2															
1:1993	AV-HM25	Frequency, Hz		63	125	250	500	1000	2000	4000	8000	Н	М	L	SNR
Ë		Mean attenuation, dB		13.6	13.4	18.3	26.8	35.5	33.2	32.8	33.2	30	25	17	28
		Std. Deviation		3.2	3.4	2.4	2.8	3.4	4.0	2.6	3.4	30			
O	100		1100						TIM						

13.1 19.8 29.3 37.6

250 500 1000 2000 3150 4000 6000 8000

33.3 36.3 36.6 35.6

36.7



This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT EP 3007-3.2



H M L NRR