



High Filtration Dust Mask - FFP2

Article No.: 27106AV187

Flat Fold High Filtration Dust Mask with Exhalation Valve, Contour Design, Bendable Nosepiece.

AVES®FFP2 respirator masks are made for working environments in which deleterious and mutagenic particles can be found in the breathing air.



EN 149:2001
+A1:2009

CE 0086


- CE Certified according to European Council Directive 89/686/EEC and subsequent amendments
- Certified to European Standard EN 149:2001+A1:2009 - Class FFP2 NR D
- Single piece packed offering higher hygiene levels for usage
- Qualified to Dolomite Clogging Test



MICRO FILTRATION

EXHALATION VALVE

WELDED EDGE SEAL



Tough design outer shell



Exhalation valve



Bendable Concealed Nosepiece



Welded edge seal



Welded strap holder



Elastic strap with clip

Accommodates a wide range of safety equipment, including eye, ear, & face protection.



Recommended Applications:

Sanding, sweeping, bagging, grinding and other operations that create dust. Uses would also include solids such as those from oil & petrochemical industries, textile industry, chemicals industry, surface preparation, food preparation and handling, woodworking, grain handling and milling, process of minerals and other substances.

It can prevent harmful pollutants such as nonferrous metals, heavy metals...etc, and separate harmful material such as glass fiber, asbestos...etc.

Doc. Control:	Rev.: 3.2	Date: April 6, 2016
---------------	-----------	---------------------

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT RP 4001-3.2






High Filtration Dust Mask - FFP2

Article No.: 27106AV187

TECHNICAL FEATURES

- 1 Micro Filtration**
 - Advance microfibers with high transpiration range
- 2 Concealed Bendable Nosepiece**
 - Upholds its shape well during use
 - Reduced metal components
- 3 Exhalation Valve**
 - Eliminates exhaled air and reduces moisture buildup inside respirator
 - Allows easier breathing and improves hygiene.
- 4 Welded Edge Seal**
 - Ensures no open layer around the edges
- 5 Strong Elastic Head Strap**
 - Ensures the best seal and secure fit with minimum leakage
 - With adjustable clip & strap holder on side



Standard:	EN 149:2001 + A1:2009 FFP2 NR D
Size:	Standard Size
Color:	Natural White
Packing:	10pcs per box, 40 boxes per carton

IMPORTANT:

Use of respirators against solid and liquid aerosols are classified according to one of three categories – **FFP1, FFP2, and FFP3**.

APPLICATIONS:

- **FFP1:** Protection against non-toxic solid & liquid aerosols (e.g. oil-mists) in concentrations up to 4.5 x MAC/OEL/TLV or 4 x APF.
- **FFP2:** Protection against non-toxic and low-to-average toxicity solid and liquid aerosols (e.g. oils-mists) in concentrations up to 12 x MAC/OEL/TLV or 10 x APF.
- **FFP3:** Protection against non-toxic, low-to-average toxicity and high toxicity solid & liquid aerosols (e.g. oil-mists) in concentrations up to 50 x MAC/OEL/TLV or 20 x APF.

WARNING!

- This product does not eliminate the risk of contracting any disease or infection.
- Failure to follow all instructions and limitations on the use of this product could reduce the effectiveness of respirator and result in sickness or death.
- A properly selected respirator is essential to protect your health. Before using this respirator, consult an industrial hygienist or occupational safety professional to determine the suitability for your intended use.
- This product does not supply oxygen. Use only in adequately ventilated areas containing sufficient oxygen to support life. Do not use this respirator when oxygen concentration is less than 19.5%.
- Do not use when of contaminants are immediately dangerous to health or life.
- Leave work area immediately and return to fresh air if (a) breathing becomes difficult, or (b) dizziness or other distress occurs.
- Facial hairs or beards and certain facial characteristics may reduce the effectiveness of this respirator.
- Never alter or modify this respirator in any way.
- Only for single use. No maintenance necessary. Discard the respirator after single use.
- Keep respirators in the display box away from direct sunlight until use.

NOTE: **MAC** = Maximum Admissible Concentration
TLV = Threshold Limit Value

OEL = Occupational Exposure Limit
APF = Assigned Protection Factor

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT RP 4001-3.2

Doc. Control:	Rev.:	Date:
	3.2	April 6, 2016

