



ALUMINIZED GLOVES

Article No.: HG-7085

HG-7085 is a Multilayer Aluminized gloves that provide superior protection from extreme radiant temperatures, sparks, and molten metal splash. HG-7085 has palm and thumb construction for radiant heat protection and protection from direct contact with objects up to 2000°F / 1095°C.



- Heat Resistant
- Abrasion Resistant
- Tear Resistant



Contact Temperature
Up to
1095 °C

NOTE:

- The peak temperature rating for this item represents the heat resistance of the palm of the glove.
- The aluminized surface is not recommended for direct contact with temperatures above 350°F (175°C).

SPECIFICATIONS

- Fiber type:** Texturized Fiberglass
- Coating:** Aluminized
- Contact Temperature:** 1095 °C (2000 °F)
- Operating Temperature:** 815 °C (1500 °F)
- Radiant Heat Resistance:** 1650 °C (3000 °F)
- Length:** 14" (35.56 cm)
- Size:** One Size Fits All
- Color:** Aluminized Silver
- Packing:** 12 Pairs/box

APPLICATIONS

- Foundry & glass operations, welding, hot works, industrial and proximity fire fighting.

INTERNATIONAL STANDARDS

 CAT III	 EN 388 3 X 4 X	Abrasion Resistance 0 1 2 3 4 Cut Resistance 0 1 2 3 4 5 Tear Resistance 0 1 2 3 4 Puncture Resistance 0 1 2 3 4
	 EN 420	Flammability 0 1 2 3 4 Contact heat 0 1 2 3 4 Convective heat 0 1 2 3 4 Radiant heat 0 1 2 3 4 Small molten metal splashes - N A - Large molten metal splashes - N A -
	 EN 407 4344XX	

Doc. Control:	Rev.: 3.2	Date: March 22, 2016
---------------	-----------	----------------------

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT HG 5169-3.2

