



DOUBE LAYER BALACLAVA

Article No.: 1631AE52

Innovative protective fabric that offers incredible softness, has a lightweight feel and is flexible. It is designed to deliver premium protection against molten metal splash, radiant heat, flame and other smelting hazards. An outstanding value and the best choice among thermal resistant, metal-shedding fabrics, it has been chosen by leading aluminum manufacturers, worldwide, for its protection, comfort and durability.



COMPOSITION

Fabric: Oasis® 1000
Fiber Blend: 50% Lenzing FR®, 40% wool, 10% Nylon
Molten Aluminium Splash: Level D3
Molten Iron Splash: Level E3
Weight: 339 gsm or 10 oz

STYLE & DESIGN

- Double layer
- Breathable fabric
- Double stitched and bartacked stress points
- Can cover nape and neck all around
- Can be underwear before helmet or other head/face protection against heat.



INTERNATIONAL STANDARDS

- EN ISO 11612:2008 (A1,B1,C1,D2,E2,F1)
- A1 - Limited Flame Spread (EN ISO 15025)
- B1 - Convective Heat (EN 9151)
- C1 - Radiant Heat (EN 6942)
- D3 - Molten Aluminum Splash (EN 9185)
- E3 - Molten Iron Splash (EN 9185)
- F1 - Contact Heat (EN 12127)



PPE CUSTOMIZATION PROGRAM

Doc. Control:	Rev.:	Date:
	3.2	April 4, 2016

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT FR 6149-3.2

