

GLYPTEC®

SERVICE MASTER® 3000

Article No.: 63219GT562

SERVICE MASTER® 3000 Coverall is made of advanced plastic film plus a unique non-woven fabric. Conforms to CE Category 3 Type 3, 4, 5 & 6, Antistatic to EN1149 and protects against radioactive particles as per EN1073.2.

Guaranteed to provide an extremely effective barrier against both inorganic chemicals and biological hazards. The design is offering increased mechanical strength, liquid and particulate protection.



■ EXCELLENT BARRIER PROTECTION

SERVICE MASTER® is very effective in holding out dust particles and chemicals to meet with 5/6 standards - even better than its predecessor.

■ HIGHER COMFORT

SERVICE MASTER® is lighter and even more breathable than before and certainly the most comfortable 5/6 product on the market.

■ ENVIRONMENTALLY FRIENDLY

SERVICE MASTER® uses 20% less raw materials than any other product on the market whilst offering better barrier.

SERVICE MASTER® 3000 FEATURES

- **ROBUST LIGHTWEIGHT PROTECTION**
- **EXCEPTIONAL LIQUID DEFENSE** (Unique seam stitching)
- **AEROSOL RESISTANT**
- **OUTSTANDING BREATHABILITY**
- **EXCEPTIONAL FIT** (Greater ease of movement)
- **ANTI-STATIC TREATMENT**
- **COMFORTABLE DESIGN**
- **SILICON-FREE**
- **ULTRA LOW LINTING**



CAT III
CE 0624

Doc. Control:	Rev.:	Date:
	3.2	April 9, 2016

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT FR 6050-3

A PRODUCT OF

PROTECTIVE LINE

SERVICE MASTER® 3000
Article No.: 63219GT562


Chin Protection which fit for the mask and resperitor better



Double way heavy duty zipper



Double storm flap resealable with adhesive tape



Elastic band thumb loop

STYLE & COMPONENTS

Hood, elastic band at hood, cuffs, wasit back and ankles, double way-zipper, resealable double storm flap, with self-adhesive tape, full impermeable tape seams, thumb loop for secure fit.

STANDARDS

- CE 0302 Cat III
- EN ISO 14605:2005+A1:2009 (T3)
- EN ISO 14605:2005+A1:2009 (T4)
- EN ISO 13982-1:2004+A1:2010 (T5)
- EN 13034:2005+A1:2009 (T6)
- EN 14126:2003
- EN 1149-5:2008
- EN 1073-2:2002

APPLICATIONS

- Industrial & Petrochemical
- Agriculture & Farm Pesticide
- Abattoirs
- Asbestos Handling
- Car Industry
- Clean Room Farming
- Food Processing Industry
- Maintenance and Repairs
- Medical / Emergency Services
- Pharmaceutical
- Police - Scene of Crime
- Forensic Science
- Technology Industry
- 2-Pack Paint Spray
- Waste Management Services

SIZE CHART

HEIGHT		
S	164-170cm	(5'4" - 5'6")
M	167-176cm	(5'5" - 5'9")
L	174-181cm	(5'8" - 6')
XL	179-187cm	(5'11" - 6'2")
2XL	186-194cm	(6'1" - 6'4")
3XL	194-200cm	(6'3" - 6'6")
CHEST		
S	84-92cm	(33" - 36")
M	92-100cm	(36" - 39")
L	100-108cm	(39" - 42")
XL	108-115cm	(42" - 45")
2XL	115-124cm	(45" - 49")
3XL	124-132cm	(49" - 52")

DONNING



DOFFING



Doc. Control:	Rev.:	Date:
	3.2	April 9, 2016

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval.



A PRODUCT OF

 PROTECTIVE LINE